

RGB LED PAR64 SPOTLIGHT

Suitable for architectural and stage applications, the PAR64 casts RGB or White light output.



Features

- For indoor and outdoor use
- DMX-512 control
- Includes DMX outdoor rated cable input and output + 120V wire lead + waterproof connectors

Operation

Can be operated in one of three ways:

- 1) **Onboard Control** (standalone)
- 2) **DMX Mode**
- 3) **Daisy Chain** (max. 10 units)

Applications

Architectural | Stage | Landscape | Accent



Voltage	100-240V AC
Wattage	40W
Color Temp	RGB or White*
# of LEDs	36 High Power RGB LEDs
Lumens	2200
Beam Degree	30°
Housing	Die-cast aluminum housing with tempered glass
Working Temp	-30°C~+50°C
Rotation Angle	180°
Plug/Connector	120V Lead: 56" (142cm) Output Connector: 20" (51cm)
Lifespan	+60,000 hours
Warranty	3-years


*Custom color temperature available in WW + WH

Housing



Black






Dimensions




Ordering Codes

	Product		Color Temp
LS-	PAR64	-	RGB
RGB: Multi-color			

Accessories

Image	Code	Product	Description
	LS-NA-Plug	Plug	North American 3-prong plug
	LS-5M-DMX-EXT	5M Extension Cable	5M (16.4') DMX extension cable, outdoor rated connections
	LS-30M-DMX-EXT	30M (100') Extension Cable	25M (82') DMX extension cable, outdoor rated connections
	LS-DMX-WC-RGBW	DMX WiFi Controller	With pre-programmed modes and built-in WiFi router, the RGBW DMX controller provides full control and customization of your lighting experience. <i>Review spec sheet for more information.</i>
	LS-RGB-DMX-W2	DMX Wireless Controller	Transmits and receives DMX wireless signal, for DMX solid state lighting. 9-12VDC, 120V Power Supply included. <i>Review spec sheet for more information.</i>

Illuminance at a Distance



Note: The curves indicate the illuminated area and the average illumination when the luminaire is at a different distance.