





Date: Project:
Notes:

24V LINKABLE LED LINEAR LIGHT

An LED under cabinet fixture available in three sizes with aluminum housing and hot spot free design.

Features

- Plug & Play 24V system
- Max length of 20' per power feed
- Even illumination No hot spots
- Multiple ways to mount
- Easily connect together for larger applications
- Includes x2 surface mount clips

Applications

Task | Under Cabinet | Display

Installation

Surface mount installation with surface mounting clips, 45° angle clips or 3M tape





Length	6" (15cm)	12" (30cm)	40" (100cm)
Voltage	24V DC		
Wattage	3W	5W	15W
Color Temp	3000K / 4000K		
CRI	>92		
Lumens	225	410	1100
Beam Degree	120°		
Dimmable	Yes		
Housing	Aluminum		
Lifespan	+60,000 hours		
Warranty	3-year		

Dimensions

Ordering Codes

	Product	Length	Color Temp
LS -	LL50	-	-
		6 : 6 inches	3K : 3000K
		12 : 12 inches	4K : 4000K
		40 : 40 inches	

Accessories

Image	Code	Product	Description
	LS-LL50-FC	Surface Mount Clips	Included. Flat 180° mounting clips for LL50. 2 pieces in a set.
7	LS-LL50-IP	Input Power Feed	Input connector from 24V DC power supply to LL50 LED light.
d	LS-LL50-TS	Touch Switch	24V DC Touch Switch plugs directly into LL50.
100	LS-LL50-MC	Middle Connector	Middle connector to join two lengths seamlessly together for LL50.
The said	LS-LL50-CC	Corner Connector	Corner Connector for LL50. Available for right corners or left corners.
	LS-LL50-JC	Jump Connector	Corner connector with 20" wire lead in middle for connecting two LL50's together.
	LS-LL50-AC	45° Angle Clip	Angled 45° mounting clips for LL50 .
31.31.31.31	LS-LL50-3M	3M Tape	Double-sided 3M tape to easily mount LL50.