

Date:

Project:

Notes:

CURVED 2835 FLEXIBLE LED STRIP LIGHT

For taking angles around corners, curves and irregular layouts, the ultra thin curved LED strip can bend vertically and horizontally. Suitable for signage, channel letters or cove, this LED tape light runs up to roll lengths of 5M (16.4').

Features


- Curved ultra thin flexible strip can take angles instead of cutting
- Highest quality 2835 SMD LEDs
- Maximum Length: 5M (16.4')
- 12V DC input
- Excellent color output, CRI >85
- 852 lumens per meter
- Cuttable every 50mm
- Dimmable with our dimmable low voltage power supplies

Applications

Signage | Channel Letters | Cove


Installation

Double-sided 3M tape on the back



Voltage	12V DC
Wattage	7.2W/M (2.2W/FT)
Roll Length	5M (16.4')
Cut Distance	3 LEDs - 50mm (2")
# of LEDs	72 LEDs/M (22 LEDs/FT)
Color Temp	3000K / 3500K / 5000K / Red / Green / Blue
CRI	>85
Lumens	852/M (260/FT)
Beam Degree	120°
Dimmable	Yes
Lifespan	+65,000 hours
Warranty	5-year

Dimensions



Ordering Codes

Product

LS -

FLI

FLI : Indoor

-

Chip & Length

2B

2 : 2835 B : 5M (16.4')

-

Voltage

12

12 : 12 volt

-

LEDs/M

72

72 : 72 LEDs





-

Color Temp

3K : 3000K
35K : 3500K
5K : 5000K
R : Red
G : Green
B : Blue

Solderless Connectors

Solderless connectors are designed to provide a simple and quick connection for projects. Suitable for indoor applications.

Image	Code	Product	Description
	LS-SC1-3528	Seamless Connector	2 wire. Width: 1/2" (13mm). Application: Add length.
	LS-SC2-3528	Connector on one End	2 wire. Width: 1/2" (13mm). Applications: Cut strip to power.
	LS-SC3-3528	Connector on both Ends	2 wire. Width: 1/2" (13mm). Applications: For corners.
	LS-SC7-3528	Block Connector	2 wire. L7/16 x W3/8 x H5/16" (L11 x W10 x H8mm). Applications: For strip to strip or strip to power.