

Dimmable 24W, 45W & 60W LED Power Supplies



Product Code	LS-24D-CV	LS-45D-CV	LS-60D-CV *LS-24V-60D-CV
Input	120V AC	120V AC	120V AC
Output	12V DC	12V DC	12V / 24V
Wattage Amperage	24W 2A	45W 3.75A	60W (5A-12V) 60W (2.5A-24V)
Working temperature	4°F (-20°C) to 104°F (40°C)	4°F (-20°C) to 104°F (40°C)	4°F (-20°C) to 104°F (40°C)
Dimensions	L1 ^{17/32"} (155mm) W2 ^{1/8"} (54mm) H2 ^{5/32"} (20mm)	L7 ^{3/32"} (180mm) W2 ^{13/32"} (61mm) H6 ^{3/64"} (25mm)	L7 ^{3/32"} (180mm) W2 ^{23/64"} (60mm) H1 ^{3/8"} (35mm)

Damp location rated

24W | 45W | 60W

Class 2 rated
Hardwire install

Note: *24V Dimmable LED driver only stocked in 60W version

Wide-range compatibility with all classes of dimmers and lighting controllers



Applications

Used with 12V DC Products:

- Cabinet Lighting
- Flexible Strip Lighting
- Signage Lighting
- Outdoor Lighting

Technical data

- Smooth full range dimming performance
- No minimum load
- Microprocessor controlled for smooth fade-on/off
- Direct wire hook-up installation
- Suitable for use in dry and damp locations
- cETLus Certified to **CSA & UL** Standards

120V AC Input



12 & 24V DC Out-



- **Dimmable through line voltage side**

Requires no minimum load - Direct wire hook-up installation- **Suitable for use in dry and damp locations.**

