



Aluminum Profiles for LED Flex

Corner mount




LL8

Square modern



LL9

Slim recessed



LL10

Product Code	LS-LL8-L1 LS-LL8-L2	LS-LL9-L1 LS-LL9-L2	LS-LL10-L1 LS-LL10-L2
Length	L40" (1M) L80" (2M)	L40" (1M) L80" (2M)	L40" (1M) L80" (2M)
Lens	*Frosted or Opaque <small>*1M (3.28') or 2M (6.56') Lenses available</small>	*Frosted or Opaque <small>*1M (3.28') or 2M (6.56') Lenses available</small>	*Frosted or Opaque <small>*1M (3.28') or 2M (6.56') Lenses available</small>
Dimensions	W5/8" (W16mm)	W5/8 x H15/32" (W16 x H12mm) Router: W43/64 x H15/32" W17mm x H12mm	W19/32 x H15/64" (W15 x H6mm) Router: W15/32" x H15/64" W16mm x H6mm
Material	Anodized Aluminum	Anodized Aluminum	Anodized Aluminum
Installation	Surface corner	Recessed / Surface	Recessed / Surface
Compatible strips	Indoor & Outdoor Flex <small>Except: RGBW & RGBW MP</small>	Indoor & Outdoor single color Flex <small>Except: RGBW & RGBW MP</small>	Indoor & MP Flex <small>Except: RGBW & RGBW MP</small>
Compatible Solderless connects	3528 / 5050 / 2835 / RGB	Production lead or solder	Production lead or solder

Applications

- Under cabinet
- Bathroom
- Closet
- Under cabinet
- Railings
- Display
- Shelving
- Back bar
- Work-space

Aluminum Profiles for LED Flex


Low profile surface




Thin recessed or surface




Deep recessed



LL11



LL15



LL16

Product Code	LS-LL11-L1 LS-LL11-L2	LS-LL15-L1	LS-LL16-L1
Length	L40" (1M) L80" (2M)	L40" (1M)	L40" (1M)
Lens	*Frosted or Opaque *1M (3.28') or 2M (6.56') Lenses available	Frosted, Opaque & Clear *1M (3.28') or 2M (6.56') Lenses available Frosted or opaque available	Frosted, Opaque & 1M (3.28') or 2M (6.56') Lenses available Frosted or opaque available
Dimensions	W1 ³ / ₁₆ x H9/ ₃₂ " W30 x H7mm	W63/64 x H9/ ₃₂ " (W25 x H7mm) Router: W45/64 x H15/64" W18 x H6mm	W63/64 x H19/ ₃₂ " (W25 x H15mm) Router: W3/4 x H35/64" W19 x H14mm
Material	Anodized Aluminum	Anodized Aluminum	Anodized Aluminum
Installation	Surface mount	Recessed / Surface	Recessed / Surface
Accessories	End caps & Mounting Clips	End caps & Mounting Clips	End caps & Mounting Clips
Compatible Strips	All Indoor & MP Flex Except: RGBW & RGBW MP	All Indoor & MP Flex Except: RGBW & RGBW MP	All Indoor & Outdoor Flex Except: RGBW & RGBW MP
Compatible Solderless connects	3528	3528	3528

Applications

- Cabinet
 - Display
 - Shelving
- Under cabinet
 - Closet
 - Hand rail
- Shelving
 - Work-space
 - Ceiling & wall

Aluminum Profiles for LED Flex


Wide Slim




Inground - Walk on




Inground - Drive on



LL13



LL21



LL22

Product Code	LS-LL13-L1 (Wide Slim)	LS-LL21 (Light duty Inground)	LS-LL22-L1 (Heavy duty Inground) LS-LL22-L2
Length	L40" (1M) L80" (2M)	L40" (1M)	L40" (1M) L80" (2M)
Lens	*Frosted or Opaque <small>*1M (3.28') or 2M (6.56') Lenses available</small>	Thick Frosted	Thick Frosted
Dimensions	W29/32 x H25/64" (W23 x H10mm) Router: W15/16 x 25/64" W24mm x H10mm	W3/4 x H23/64" (W19 x H9mm) Router: W25/32 x H23/64" W20 x H9mm	W1-1/32 x H1-1/32" (W26 x H26mm) Router: W1-1/16 x H1-1/32" W27 x H26mm
Material	Anodized Aluminum	Anodized Aluminum	Anodized Aluminum
Installation	Surface / Recessed	Recessed	Recessed
Accessories	End caps & Mounting Clips	End caps & Mounting Clips	End caps & Mounting Clips
Compatible Strips	All Indoor & Outdoor Flex	All Indoor & Outdoor Flex <small>Except: RGBW & RGBW MP</small>	All Indoor & Outdoor Flex <small>Except: RGBW & RGBW MP</small>
Compatible Solderless connects	All solderless connectors	Production lead or solder	Production lead or solder

Applications

- Under cabinet
 - Bathroom
 - Closet
 - Hand rail
- Walkways
 - Decks
 - Stairs
 - Walk on
- Driveways
 - Decks
 - Stairs
 - Drive on

lumenstarled.com