

LED Modules



2 Mod: **White 6000K** | **Warm white 3000K**



3 Mod: **White 6000K**



RGB



Applications

- Backlighting Signage
- Backlighting other transparent objects
- Perimeter lighting

Features

- Simple installation using 3M tape on back or with screw tabs
- 2 or 3 - 2835 High Brightness Chips/Module
- Outdoor rated
- Durable & Long Lasting
- 8cm (3.1") wire between modules



	2 Module	3 Module
Product Code	LS-LM-2-6K LS-LM-2-3K	LS-LM-3-6K LS-LM-RGB
Voltage	12V DC	
Wattage	0.66W - 2 Mods 1.02W - 3 Mods 0.75W - RGB Mods	
# of LEDs	2 or 3 - 2835 SMD LEDs 3 - 5050 SMDs for RGB	
Housing	Thermal Resistant PC	
Color Temperature	Warm white (3000K) White (6000K) *RGB (Red, Green, Blue) *4 Wire RGB system	
Lumens	55 - 2 Mods 75 - 3 Mods	
2 Mod: 3 Mod: RGB:	L1 ^{17/32} x W19/32 x H7/16" (L39 x W15 x H11mm) L2 ^{13/32} x W19/32 x H7/16" (L61 x W15 x H11mm) L3 ^{1/2} x W1/2 x H1/4" (L89 x W12.7x 6.35mm)	
Total Length	12.5ft length includes 25 modules 3" (76.2mm) wire length between modules	