

## RGB DMX Controller



- Control up to 170 fixtures
- 40+ built-in programs with adjustable parameter
- Timing On/Off
- Includes remote

|                     |   |
|---------------------|---|
| Product Code        | LS-DMX-SIM  |
| Voltage             | 120V AC   |
| Wattage             | 3W  |
| IP Protection       | 20  |
| Receiver Size       | L6 <sup>1/2</sup> x W4 <sup>9/64</sup> x H1 <sup>57/64</sup><br>L165 x W105 x H48mm |
| Working Temperature | -20°C ~ +50°C   |
| Surface Mountable   | Yes   |

## RGB DMX Console



|                 |  |
|-----------------|--|
| Product Code    | LS-DMX-Console   |
| Voltage         | 120 - 240V AC Input  |
| Output terminal | XLR-3  |
| Dimensions      | L 21 x W7 <sup>9/32</sup> x H3 <sup>15/16</sup><br>L535 x W185 x H100mm  |
| Features        | 192 CH, 12 Scanner,<br>16 Channels per scanner<br>8 Sliders, 6 Programmable<br>chases of 240 Scenes<br>Power failure memory &<br>Blackout protection |

## RGB DMX Touch Controller



**Mounting:**  
Fits - Single or  
double gang  
Junction box

### Features

- Graphical color display to show selected environment
- Color/dimmer/speed palette / Color temperature mixing
- Touch sensitive buttons. No mechanical parts
- Touch sensitive wheel allows for accurate color selection
- Multi-zone microSD memory - 32Gb Max
- Multi-room control with 500 scenes, 10 zones
- 1024 DMX channels. Control 340 RGB fixtures
- USB & Ethernet connectivity for programming and control
- RS232, Dry Contact Ports and an Infra Red input port
- Clock and calendar with Sunrise/Sunset triggering
- Network communication. Control lighting remotely

|                 |  |
|-----------------|--|
| Product Code    | LS-DMX-Touch   |
| Input Voltage   | 110 - 240V AC  |
| Output protocol | DMX512 (x2)  |
| Programmability | PC, Mac, Tablet,<br>Smartphone   |
| Connections     | USB, Ethernet,<br>RS232, Clock, 8 dry<br>contact ports, 5v Output<br>Relay |
| Memory          | microSD (32Gb Max)   |
| Mounting        | Single or double gang<br>Junction box                                      |
| Dimensions      | L5 <sup>3/4</sup> x W4 <sup>11/64</sup> x 7/16"<br>L146 x W106 x H11mm     |