



| Date: | Project: |
|--------|----------|
| Notes: | |

12V THIN RECESSED LED PANEL

For low clearance applications, available in 12V DC and is dimmable with our LED power supplies (sold separately).

Features

- Super thin profile, 1" clearance
- · Recess install only, with spring clips
- Dimmable with our LED power supplies

Applications

Office | Kitchen | Hallway | Yachts and Off the Grid

Installation

Recessed install, directly into dry wall

• **8.5W, 4"**: 4^{1/4}" (108mm) / **14W, 6"**: 6^{1/4}" (159mm)










| Diameter | 4" (102mm) | 6" (152mm) |
|-------------|----------------------------------|------------|
| Voltage | 12V DC (constant voltage) | |
| Wattage | 8.5W | 14W |
| Color Temp | 3000K / 4500K | |
| CRI | >85 | |
| Lumens | 410 | 755 |
| Beam Degree | 120° | |
| Dimmable | Dimmable with LED power supplies | |
| Housing | Aluminum | |
| Lifespan | +60,000 hours | |
| Warranty | 3-year | |

Finishes Available



White

Dimensions



Color Temp

Ordering Codes

12V Panel Light LS -

8.5W: 8.5W (4") **14W**: 14W (6")

Product

-

RD : Round

Trim

-

3K : 3000K

45K : 4500K