



Full Brightness 3000K

Dimmed 1800K



DIM TO WARM FLEXIBLE LED STRIP

Adjust the color temperature from 3000K full brightness to 1800K dimmed, like traditional lighting. For dry locations with roll lengths up to 5M (16.5').

Features

- Adjust the color temperature from 3000K to 1800K
- Highest quality 2016 SMD LEDs
- 24V DC input
- Excellent color output, CRI >90
- 1800 lumens per meter
- Maximum Length: 5M (16.4')
- Cuttable every 62.5mm
- Dimmable with our dimmable low voltage power supplies

Applications

Under Cabinet | Display | Accent | Mood

Installation

Double-sided 3M tape on the back



Voltage	24V DC
Wattage	18W/M (5.5W/FT)
Roll Length	5M (16.4')
Cut Distance	14 LEDs - 62.5mm (2 ^{7/16} "
# of LEDs	224 LEDs/M (3.28')
Color Temp	Dim to Warm (3000K dims to 1800K)
CRI	>90
Lumens	1800/M (550/FT)
Beam Degree	120°
Dimmable	Yes, dim to warm
Lifespan	+65,000 hours
Warranty	5-year

Dimensions







Ordering Codes

	Product		Chip & Length		Voltage		LEDs/M		Color Temp
LS -	FLI	-	4B	-	24	-	224	-	DTW
	FLI : Indoor		4 : 2016 B : 5M (16.5')		24 : 24 volt		224 : 224 LEDs		DTW : Dim to Warm

Solderless Connectors

Solderless connectors are designed to provide a simple and quick connection for projects. Suitable for indoor applications.

Image	Code	Product	Description
	LS-SC1-2835	Seamless Connector	2 wire. Width: 5/8" (16mm). Application: Add length.
	LS-SC2-2835	Connector on one End	2 wire. Width: 5/8" (16mm). Applications: Cut strip to power.
	LS-SC3-2835	Connector on both Ends	2 wire. Width: 5/8" (16mm). Applications: Corners.
	LS-SC7-2835	Block Connector	2 wire. L7/16 x W3/8 x H5/16" (L11 x W10 x H8mm). Applications: For strip to strip or strip to power.