

CURVED 2835 FLEXIBLE LED STRIP LIGHT

Ultra thin curved flexible strip can take angles instead of being cutting. For dry locations with roll lengths up to 5M (16.4').

Features


- Curved strip for angles
- Highest quality 2835 SMD LEDs
- 12V DC input
- Excellent color output, CRI >85
- 852 lumens per meter
- Maximum Length: 5M (16.4')
- Cuttable every 50mm
- Dimmable with our dimmable low voltage power supplies
- Dimmable with our dimmable

Applications

Signage | Channel Letters | Cove


Installation

Double-sided 3M tape on the back



Voltage	12V DC
Wattage	7.2W/M (2.2W/FT)
Roll Length	5M (16.4')
Cut Distance	3 LEDs - 50mm (2")
# of LEDs	72 LEDs/M (3.28')
Color Temp	3000K / 3500K / 5000K / Red / Green / Blue
CRI	>85
Lumens	852/M (260/FT)
Beam Degree	120°
Dimmable	Yes
Lifespan	+65,000 hours
Warranty	5-year

Dimensions







Ordering Codes

	Product	Chip & Length	Voltage	LEDs/M	Color Temp
LS -	FLI	2B	12	72	
	FLI : Indoor	2 : 2835 B : 5M (16.4')	12 : 12 volt	72 : 72 LEDs	3K : 3000K 35K : 3500K 5K : 5000K R : Red G : Green B : Blue

Solderless Connectors

Solderless connectors are designed to provide a simple and quick connection for projects. Suitable for indoor applications.

Image	Code	Product	Description
	LS-SC1-2835	Seamless Connector	2 wire. Width: 1/2" (13mm). Application: Add length.
	LS-SC2-2835	Connector on one End	2 wire. Width: 1/2" (13mm). Applications: Cut strip to power.
	LS-SC3-2835	Connector on both Ends	2 wire. Width: 1/2" (13mm). Applications: For corners.
	LS-SC7-2835	Block Connector	2 wire. L7/16 x W3/8 x H5/16" (L11 x W10 x H8mm). Applications: For strip to strip or strip to power.