

HYDRA RGB LED UNDERWATER LIGHT



The RGB Underwater Light is a small light with a swivel adjustment perfect for landscape, ponds or water features.

Features

- 316 Stainless steel housing
- Tempered convex glass
- Can choose any RGB color using control
- Choose millions of colors using RGB high power LEDs
- RGB Controls (Receiver & remote) required for full capabilities of fixture

Applications

Ponds | Water Features | Landscape | Underwater | Accent



Specifications

Voltage	24V DC
Wattage	9W
Lumens	770
Color Temp	RGB (color changing, control required)
# of LEDs	3 x 3W RGB LEDs (3 in 1)
IP	68
Lifespan	+50,000 hours
Beam Degree	25°
Dimmable	Yes
Housing	316 Stainless Steel
Dimensions	4 1/2" (114mm) x 6" (152mm)
Wire Length	10' (3M)
Warranty	3-year

Finishes Available



Stainless Steel




Ordering Codes

Product: UW Color Temp: RGB
 LS - UW - RGB
RGB : Multi-color

Power Supplies

Image	Code	Voltage	Output Power	Class II	Dimmable Specs
Non-Dimmable					
	LS-24V-30W-O-CV	24V	Max. 30W	√	N/A
	LS-24V-60W-O-CV	24V	Max. 60W	√	N/A
	LS-24V-96W-O-CV	24V	Max. 96W	x	N/A

Accessories

Image	Product	Code	Description
	100' Outdoor Wire	LS-OW-16-2-100	100' (30.5M) Outdoor wire for led lights. 16-2 AWG
	100' Outdoor RGBW Wire	LS-RGBW-OW-16-5	100' (30.5M) RGBW Outdoor wire for RGB and RGBW led lights. 16-5 AWG
	Outdoor Rated Marettes	LS-GEL-MAR	Outdoor rated, gel filled marettes ensure secure electrical connections in outdoor and wet conditions. Pack of 2.

RGB Controllers & Receivers

Image	Product	Code	Description	Functions	Dimensions
	RGB Handheld Remote	LS-RGB-MZR	Controls RGBW LED Lights, 868 Mhz	Multizone (4), 3 Presets, Dimming, Fade/Flash/Jump, Custom colors	L4 ^{3/4} x W2 ^{3/16} x H1 ^{1/16} " (L120 xW55 x H17mm)
	RGB Wall Mount Remote	LS-RGB-MZWMR	Controls RGB or RGBW LED Lights, 12-24V DC Input, 2.5-5W, 868 MHz Fits single gang box. Includes 6W driver, 50ft wireless range.	3 Presets, Dimming, Fade/Flash, Custom colors, includes 10 pre-loaded programs	L4 ^{3/4} x W2 ^{15/16} x H1 ^{1/8} " (L120 xW75 x H29mm)
	Casambi 4 Channel PWM Controller	LS-CBU-PWM4	Control up to 250 fixtures with intelligent mesh network and customizable user interface. Multiple networks can be set up with same control system	12-24V DC 48W - 96W 4A Output Power Surface Mountable Includes Downloadable Smart Device App	L2-7/8 x W1-3/16 x H11/16" (L72.6 x W30 x H18mm)
	Tuya Control	LS-RCV-SMZ8A-TY	Receiver for RF remotes (RGB / RGBW / CCT / SC) Wifi Capable with free control app	12-24V / 36V / 48V 5 x 8A/Ch / 5 x 6A/Ch / 5 x 4A/Ch 5x96W / 5x192W / 5x216W 15M (50') Remote Range	L6-11/16 x W2-5/16 x 1-1/8" (L170 x W59 x H29mm)
	Outdoor MZ LED Receiver	LS-RCV-O-MZ5A	Receiver for RF Remotes (RGB/RGBW). Wifi Capable. Outdoor rated for harsh environments	12-36V DC 4 x 5A/Channel 4x(60-180W) Output Power 15M (50') Remote Range	L7 ^{1/8} x W2 ^{15/16} x H1 ^{1/2} " (L180.5 xW74x H38mm)
	Digital DMX512 Decoder	LS-DMX-DIG-DCR	Converts DMX signal for use with low voltage RGB & RGBW LED lights.	Total 5 PWM output channels, common anode. DMX channel quantity from 1CH~5CH settable.	L6 ^{7/16} x W2 ^{7/8} x H1 ^{1/2} " (L164 xW73 x H38mm)