

JOB#

E26 Medium Base Decorative Bulbs



S14 - Frosted
LS-E26-S14-FRST-27K
120V AC, 1.4W
Ø1-3/4 x H3-1/4"
Dimmable



S14 - Clear
LS-E26-S14-CLR-27K
120V AC, 1.4W
Ø1-3/4 x H3-1/4"
Non-dimmable



S14 - Filament
LS-E26-S14-FIL-27K
120V AC, 1.4W
Ø1-3/4 x H3-1/4"
Dimmable
Not for use direct to element



S11 - Frosted
LS-E26-S11-FRST-28K
120V AC, 1W
Ø1-9/16 x H2-5/8"
Dimmable



S11 - Clear
LS-E26-S11-CLR-28K
120V AC, 1W
Ø1-9/16 x H2-5/8"
Non-dimmable



E12 Candelabra Decorative Bulbs



S6 - Clear
LS-E12-S6-28K
120V AC, 1W
Ø3/4 x H1-15/16"
Non-dimmable



G8 - Frosted
LS-E12-G8-FRST-28K
120V AC, 1W
Ø1 x H1-3/4"
Non-dimmable



G8 - Clear
LS-E12-G8-CLR-28K
120V AC, 1W
Ø1 x H1-3/4"
Non-dimmable



S11 - Frosted
LS-E12-S11-FRST-28K
120V AC, 1W
Ø1-9/16 x H2-5/8"
Non-dimmable



S11 - Clear
LS-E12-S11-CLR-28K
120V AC, 1W
Ø1-9/16 x H2-5/8"
Non-dimmable

Sockets



E26 Phenolic Socket
LS-E26-SKT
120V AC, 660W max, E26 base
Ø1-3/8" cutout size
PC material



E26 Porcelain Socket
LS-E26-SKT-C
120V AC, 660W max, E26 base
Ø1-1/4" cutout size
Porcelain material



E12 Socket
LS-E12-SS2
120V AC, 60W max, E12 base
Ø7/8" cutout size
PC material

