





JOB#

STEP LIGHTS



RT05 Louver
LS-RT05
2.2W, 12V DC / 100-240V AC
Standard single gang junction box
Horizontal and vertical louver



RT05 Screwless Recessed
LS-RT05-RH
2W, 12V AC/DC / 100-120V AC
Standard single gang junction box



RD10 Scoop
LS-RD10-4W
4W, 12V DC
Ø2-3/4 x H3/4"
Recessed or surface mount



RD12 M2 Scoop
LS-RD12-2
0.5W, 12V DC
Ø1-1/2 x H1"
Fully sealed for outdoor use



RD12 M1 Scoop
LS-RD12-1
1W, 12V DC
Ø1-1/2 x H1-1/16"
Optional inground sleeve



DeckStar
LS-RD30-3K
0.5W, 12V DC
Ø1 x H11/16"
Trimless recessed installation


LANDSCAPE LIGHTS



Path Light MO1
LS-Path-MO1
2W / 4W, 12V AC/DC (G4)
Smooth cap
12" & 18" stem height available



Path Light MO2
LS-Path-MO2
2W / 4W, 12V AC/DC (G4)
Wide light output cap
12" & 18" stem height available



Path Light LL30
LS-LL30-12-3W-27K
3W, 12V AC/DC
Powder coated stainless steel
16" stem height



Uplight
LS-SGUL-MR
5W / 7W, 12V AC/DC (MR16)
Ø2-3/8 x H6-3/4"
Includes replaceable MR16 bulb



Uplight
LS-SGUL
3W / 6W, 12V AC/DC
Ø2 x H4"
Includes 15° & 40° lenses



Hardscape
LS-HS-2W-BK-3K
2W, 12V AC/DC
Stainless steel 316 housing
Includes black trim + 27K filter lens



RD13 Inground
LS-RD13-3W
3W, 12V DC Power LED
Stainless steel housing
Multiple trim styles available



COB Inground
LS-GUL-MR
5W / 7W, 12V AC/DC (MR16)
Ø4 x H5-3/8"
Die-cast brass housing



Outdoor Flexible Strip
LS-FLO-1B-12-60
4.8W/M (1.5W/ft), 12V DC
60 LEDs/M, 3528 SMD LEDs
Waterproof silicone jacket



Waterproof Spotlight
LS-UW-MR
7W, 12V AC/DC (MR16)
Ø3-7/8 x H5-3/4"
Stainless steel housing



Suspended String Lights
LS-S-24-50' / LS-S-48-100'
600W max, 50' / 1200W max, 100'
24 sockets, E26 medium base
14/2 wire gauge



Non-Suspended String Lights
LS-NS-24-50' / LS-NS-48-100'
600W max, 50' / 1200W max, 100'
24 sockets, E26 medium base
14/2 wire gauge

LED POWER SUPPLIES	Code	Voltage	Wattage	Output	Dimensions	Wiring
Non-Dimming Power Supplies						
30W Outdoor LED Power Supply	LS-12V-30W-O-CV	120V AC (50-60Hz)	30W MAX Class 2	12V DC 2.5A	L7 ^{5/16} x W1 ^{1/8} x H13/16 in.	☐ HARDWIRE ☒ PLUG
60W Outdoor LED Power Supply	LS-12V-60W-O-CV	100-265V AC (50-60Hz)	60W MAX Class 2	12V DC 5A	L7 ^{7/16} x W1 ^{7/8} x H1 ^{5/16} in.	☐ HARDWIRE ☒ PLUG
96W Outdoor LED Power Supply	LS-12V-96W-O-CV	100-265V AC (50-60Hz)	96W MAX	12V DC 8A	L7 ^{5/16} x W2 ^{11/16} x H1 ^{3/4} in.	☐ HARDWIRE ☒ PLUG
150W Outdoor LED Power Supply	LS-12V-150W-O-CV	100-240V AC (50-60Hz)	150W MAX	12V DC 12.5A	L9 ^{7/16} x W2 ^{13/16} x H1 ^{3/4} in.	☐ HARDWIRE ☒ PLUG
264W Outdoor LED Power Supply	LS-12V-264W-O-CV	100-277V AC (50/60Hz)	264W MAX	12V DC 22A	L8 ^{15/16} x W3 ^{5/8} x H1 ^{7/8} in.	☒ HARDWIRE ☐ PLUG
Landscape LED Power Supply with Photocell & Timer	LS-12AC-150W-LPS	120V AC (60Hz)	150W MAX	12V AC 12.5A	L6 ^{7/8} x W4 x H3 ^{15/16} in.	☐ HARDWIRE ☒ PLUG


ACCESSORIES



Waterproof Marrets
LS-Gel-Marr
For outdoor connections
Sold in sets of 2



Outdoor Wire
LS-OW-12-2
Custom length 12AWG
Sold by the meter



12V AC to DC Converter
LS-CONV-12AC-12DC-36W
10-28V AC or 15-40V DC input
12V DC, 3A output
36W Max Load



Waterproof Junction Box
LS-JB3
450V AC, 24A input
3 Way junction box
Full Weatherproof rating IP68

INSTALLATION

