



## DIM TO WARM LED STRIP LIGHTING



**LS-FLI-4B-24-224-DTW** 224 LEDs/M | 24V DC | 18 W/M | 5M | 2016 Chips | 62.5mm cut length | W12 x H1.5mm



## ALUMINUM CHANNELS




**Slim Modern**  
**LS-LL12-L1 (1M) / LS-LL12-L2 (2M)**  
W18 x H8mm  
Recessed or Surface mount




**Wide Modern**  
**LS-LL13-L1 (1M) / LS-LL13-L2 (2M)**  
W23 x H10mm  
Recessed or Surface mount



**Mud In**  
**LS-LL23-DW-L3 (3M)**  
W63 x H14mm  
Recessed



**Thin Recessed**  
**LS-LL15-L1 (1M) / LS-LL15-L2 (2M)**  
W25 x H7mm  
Recessed or Surface mount



**Deep Recessed**  
**LS-LL16-L1 (1M) / LS-LL16-L2 (2M)**  
W25 x H15mm  
Recessed or Surface mount

## DIMMER & PLUG



**Dimmer LS-WD-WT**  
Dimmer with switch & paddle wheel  
120V AC, 60Hz, Single Pole  
150W max load  
Fits single gang junction box



**Plug LS-120V-SWITCH**  
8ft plug with rotary switch

## 24V DIMMABLE DRIVERS (cETLus)

|                                             | SKU             | VOLTAGE           | WATTAGE         | OUTPUT       | DIMENSIONS          | WIRING:                                                                    |
|---------------------------------------------|-----------------|-------------------|-----------------|--------------|---------------------|----------------------------------------------------------------------------|
| <b>24W LED Power Supply</b>                 | LS-24V-24D-CV   | 120V AC (60Hz)    | 24W MAX Class 2 | 24V DC 1A    | L155 x W54 x H24mm  | <input checked="" type="checkbox"/> HARDWIRE <input type="checkbox"/> PLUG |
| <b>48W LED Power Supply</b>                 | LS-24V-48D-CV   | 120V AC (60Hz)    | 48W MAX Class 2 | 24V DC 2A    | L180 x W61 x H25mm  | <input checked="" type="checkbox"/> HARDWIRE <input type="checkbox"/> PLUG |
| <b>60W LED Power Supply</b>                 | LS-24V-60D-CV   | 120V AC (60Hz)    | 60W MAX Class 2 | 24V DC 2.5A  | L180 x W61 x H35mm  | <input checked="" type="checkbox"/> HARDWIRE <input type="checkbox"/> PLUG |
| <b>96W LED Power Supply</b>                 | LS-24V-96D-CV   | 120V AC (60Hz)    | 96W MAX Class 2 | 24V DC 4A    | L380 x W77 x H57mm  | <input checked="" type="checkbox"/> HARDWIRE <input type="checkbox"/> PLUG |
| <b>150W Triac Dimmable LED Power Supply</b> | LS-24V-150DE-CV | 120V AC (47/63Hz) | 150W MAX        | 24V DC 6.25A | L260 x W103 x H46mm | <input checked="" type="checkbox"/> HARDWIRE <input type="checkbox"/> PLUG |
| <b>300W Triac Dimmable LED Power Supply</b> | LS-24V-300DE-CV | 120V AC (47/63Hz) | 300W MAX        | 24V DC 12.5A | L260 x W103 x H46mm | <input checked="" type="checkbox"/> HARDWIRE <input type="checkbox"/> PLUG |

Plugs available separately