




LED Flex Tape	LED /M	Voltage	Lumens /M	CRI	Watt/M	Ordering Increment	LED Type	Cut Length	Dimensions (mm)	Colour Temp
Indoor - with 3M sticky tape on the back										
(A) LS-FLI-1B*-12-60-**-LS-FLI-1D*-12-60-**-	60	12V DC	475	>90	4.8	*5M (16.4') *25M (82')	3528	50mm	W8 x H1.5	2700K, 3000k, 4000k, 5000k, Red, Green, Blue
(A) LS-FLI-1D-24-60-3K	60	24V DC	475	>90	4.8	25M (82')	3528	100mm	W8 x H1.5	3000k
(B) LS-FLI-1B*-12-120-**-LS-FLI-1D*-12-120-**-	120	12V DC	950	>90	9.6	*5M (16.4') *25M (82')	3528	25mm	W8 x H1.5	3000k, 5000k
(C) LS-FLI-2B-24-120-**-	120	24V DC	1575	>90	14.4	5M (16.4')	2835	50mm	W10 x H1.5	2700k, 3000k, 3500k, 4000k, 5000k
(D) LS-FLI-2C-24-60-**-	60	24V DC	930	>90	8.4	10M (32.8')	2835	96mm	W10 x H1.5	3000k, 4000k
(D) LS-FLI-2F-24-60-**-	60	24V DC	540	>90	6	15M (50')	2835	96mm	W10 x H1.5	2700k, 3000k, 4000k
(E) LS-FLI-2B-12-72-**-	72	12V DC	852	>85	7.2	5M (16.4')	2835	50mm	W6.5 x H1.5	3000k, 5000k Red, Green, Blue
(F) LS-FLI-1B-12-120-CCT	120	12V DC	950	>90	9.6	5M (16.4')	3528	50mm	W8 x H1.5	2600k to 6500k
(G) LS-FLI-4B-24-224-DTW	224	24V DC	1800	>90	18	5M (16.4')	2016	62.5mm	W12 x H1.5	3000k dims to 1800k
(G) LS-FLI-4B-24-224-DTW2	224	24V DC	950	>90	9	5M (16.4')	2016	62.5mm	W12 x H1.5	3000k dims to 1800k
(H) LS-FLI-6A-24-350-**-	350	24V DC	1470	>95	14.4	4M (13')	2110	20mm	W10 x H1.5	2700k, 3000k, 4000k
Moisture Proof - with silicone coating and 3M sticky tape on the back										
(I) LS-FLM-2B-24-120-**-	120	24V DC	1575	>90	14.4	5M (16.4')	2835	50mm	W10 x H3	3000k, 4000k, 5000k
(J) LS-FLM-6B-24-300-**-	300	24V DC	990	+90	18	5M (16.4')	2110	20mm	W10	3000k, 4000k
Waterproof - Jacketed. Includes clips and waterproof connector on both ends										
(K) LS-FLO-1B-12-60-**-	60	12V DC	492	>90	4.8	5M (16.4')	3528	50mm	W8 x H1.5	3000k, 5000k
(K) LS-FLO-1C-24-60-**-	60	24V DC	492	>90	4.8	10M (33')	3528	50mm	W8 x H1.5	3000k
(L) LS-FLO-2C-24-60-**-	60	24V DC	930	>90	8.4	10M (33')	2835	96mm	W11 x H1.5	2700k, 3000k, 4000k
(M) LS-FLO-4B-24-224-DTW2	224	24V DC	950	>90	9	5M (16.4')	2016	62.5mm	W12 x H1.5	3000k dims to 1800k


*Use the following code for desired length when applicable
 **When ordering, use designated code for color temperature:

27K : 2700K	3K : 3000K	35K : 3500K	4K : 4000K	41K : 4100K	5K : 5000K	R : Red	G : Green	B : Blue
-------------	------------	-------------	------------	-------------	------------	---------	-----------	----------

Custom lengths available. Contact us with your request.

Solderless Connectors

3528



Connector LS-SC1-3528

Lead LS-SC2-3528



Jumper LS-SC3-3528



Corner LS-SC4-3528



Block LS-SC7-3528

2835



Connector LS-SC1-2835

Lead LS-SC2-2835



Jumper LS-SC3-2835




Corner LS-SC4-2835




Block LS-SC7-2835

Aluminum Channels


Compatible strip lighting* (Indoor/Outdoor/MP=Moisture Proof) and solderless connectors**




LS-LL8-L1 (1M) / LS-LL8-L2 (2M)
*3528 / 3528-OUT / 2835 / 2835-MP
**All connectors




LS-LL9-L1 (1M) / LS-LL9-L2 (2M)
*3528 / 3528-OUT / 2835 / 2835-MP
**Production lead or solder required




LS-LL9D-L1 (1M)
*3528 / 3528-OUT / 2835 / 2835-MP
**Production lead or solder required




LS-LL10-L1 (1M) / LS-LL10-L2 (2M)
*3528 / 2835 / 2835-MP
**Production lead or solder required




LS-LL11-L1 (1M) / LS-LL11-L2 (2M)
*3528 / 2835 / 2835-MP
**3528





LS-LL12-L1 (1M) / LS-LL12-L2 (2M)
*3528 / 3528-OUT / 2835 / 2835-MP
**All connectors




LS-LL13-L1 (1M) / LS-LL13-L2 (2M)
*3528 / 3528-OUT / 2835 / 2835-MP
**All connectors




LS-LL23-DW-L3 (3M)
*3528 / 3528-OUT / 2835 / 2835-MP
**All connectors




LS-LL15-L1 (1M) / LS-LL15-L2 (2M)
*3528 / 2835 / 2835-MP
**Production lead or solder required



LS-LL16-L1 (1M)
*3528 / 3528-OUT / 2835 / 2835-MP
**Production lead or solder required



LS-LL21-L1 (1M)
*3528 / 3528-OUT / 2835 / 2835-MP
**Production lead or solder required



LS-LL22-L1 (1M) / LS-LL22-L2 (2M)
*3528 / 3528-OUT / 2835 / 2835-MP
**Production lead or solder required

LED Power Supplies	Code	Voltage	Wattage	Output	Dimensions	Wiring
24V Non-Dimming Power Supplies						
30W Indoor/Outdoor LED Power Supply	LS-24V-30W-O-CV	120V AC (50-60Hz)	30W MAX Class 2	24V DC 1.25A	L7 ^{5/16} x W1 ^{1/8} x H13/16 in.	☒ HARDWIRE ☒ PLUG
60W Indoor/Outdoor LED Power Supply	LS-24V-60W-O-CV	120V AC (50-60Hz)	60W MAX Class 2	24V DC 2.5A	L4 ^{1/2} x W2 x H1 in.	☒ HARDWIRE ☒ PLUG
96W Indoor/Outdoor LED Power Supply	LS-24V-96W-O-CV	100-265V AC (50-60Hz)	96W MAX Class2	24V DC 4A	L7 ^{5/16} x W2 ^{11/16} x H1 ^{3/4} in.	☒ HARDWIRE ☒ PLUG
150W Indoor/Outdoor LED Power Supply	LS-24V-150W-O-CV	100-240V AC (50-60Hz)	150W MAX	24V DC 6.25A	L9 ^{7/16} x W2 ^{13/16} x H1 ^{3/4} in.	☒ HARDWIRE ☒ PLUG
320W Indoor/Outdoor LED Power Supply	LS-24V-320W-O-CV	100-277V AC (50/60Hz)	320W MAX	24V DC 13A	L8 ^{15/16} x W3 ^{5/8} x H1 ^{7/8} in.	☒ HARDWIRE ☐ PLUG
24V Triac/Universal Dimming Power Supplies						
24W Dimmable Indoor LED Power Supply	LS-24V-24D-CV	120V AC (60Hz)	24W MAX Class 2	24V DC 1A	L6 ^{9/16} x W2 ^{1/8} x H13/16 in.	☒ HARDWIRE ☐ PLUG
60W Dimmable Indoor LED Power Supply	LS-24V-60D-CV	120V AC (60Hz)	60W MAX Class 2	24V DC 2.5A	L7 ^{1/8} x W2 ^{3/8} x H1 ^{3/8} in.	☒ HARDWIRE ☐ PLUG
Junction Box for 24W/48W/60W Power Supplies	LS-JB-1	N/A	N/A	N/A	L13 x W3 x H1 ^{1/2} in.	PLUG available: LS-120V-SWITCH
96W Dimmable LED Power Supply	LS-24V-96D-CV	120V AC (60Hz)	96W MAX Class 2	24V DC 4A	L15 x W3 x H2 ^{1/4} in.	☒ HARDWIRE ☐ PLUG
150W Dimmable LED Power Supply	LS-24V-150DE-CV	120V AC (47/63Hz)	150W MAX	24V DC 6.25A	L10 ^{1/4} x W4 ^{1/16} x H4 ^{13/16} in.	☒ HARDWIRE ☐ PLUG
300W Dimmable LED Power Supply	LS-24V-300DE-CV	120V AC (47/63Hz)	300W MAX	24V DC 12.5A	L10 ^{1/4} x W4 ^{1/16} x H4 ^{13/16} in.	☒ HARDWIRE ☐ PLUG