

JOB#

LED STEP LIGHTS

		CHOOSE TRIM STYLE		CHOOSE FINISH - OR -		SPECIALTY TRIM		CHOOSE LIGHT COLOR	
 M2 STEP LIGHT LS-RD12-2 DIMMABLE CUTOUT: 1-3/8" DIMENSIONS: Ø1-1/16 x H1"	☐ 40MM ROUND	☐ SCOOP	☐ BLACK	☐ 70MM ROUND BLACK	☐ 1 WAY WALK ON STAINLESS STEEL	☐ 3000K	☐ RGB	CALCULATIONS WATTS: 0.5 QTY: = TOTAL WATTAGE:	
	☐ 50MM ROUND	☐ HONEYCOMB	☐ BRUSHED NICKEL	☐ 70MM ROUND BRUSHED NICKEL	☐ 2 WAY WALK ON STAINLESS STEEL	☐ 5000K			
	☐ SQUARE	☐ LOUVER	☐ WHITE	☐ SQUARE STAINLESS STEEL					
 M1 STEP LIGHT LS-RD12-1 DIMMABLE CUTOUT: 1-3/8" DIMENSIONS: Ø1-1/16 x H1-1/16"	☐ 40MM ROUND	☐ SCOOP	☐ BLACK	☐ 70MM ROUND BLACK	☐ 1 WAY WALK ON STAINLESS STEEL	☐ 2700K	☐ 4000K	CALCULATIONS WATTS: 1 QTY: = TOTAL WATTAGE:	
	☐ 50MM ROUND	☐ HONEYCOMB	☐ BRUSHED NICKEL	☐ 70MM ROUND BRUSHED NICKEL	☐ 2 WAY WALK ON STAINLESS STEEL	☐ 3000K	☐ 5000K		
	☐ SQUARE	☐ LOUVER	☐ WHITE	☐ SQUARE STAINLESS STEEL					
 MX-1 STEP LIGHT LS-RD12-2W DIMMABLE CUTOUT: 1-3/8" DIMENSIONS: Ø1-9/16 x H1-1/4"	☐ 40MM ROUND	☐ SCOOP	☐ BLACK	☐ 70MM ROUND BLACK	☐ 1 WAY WALK ON STAINLESS STEEL	☐ 3000K		CALCULATIONS WATTS: 2 QTY: = TOTAL WATTAGE:	
	☐ 50MM ROUND	☐ HONEYCOMB	☐ BRUSHED NICKEL	☐ 70MM ROUND BRUSHED NICKEL	☐ 2 WAY WALK ON STAINLESS STEEL				
	☐ SQUARE	☐ LOUVER	☐ WHITE	☐ SQUARE STAINLESS STEEL					
				INCLUDES: Replaceable 15° and 60° lenses		CALCULATIONS WATTS: 2W QTY: = TOTAL WATTAGE:			
						VOLTAGE: 12V DC WATTAGE: 2W SPREAD: 30° LUMENS: 160			

		CHOOSE TRIM STYLE		CHOOSE FINISH		CHOOSE LIGHT COLOR	
 RD10 2W STEP LIGHT LS-RD10-2W DIMMABLE CUTOUT: 2-1/4" DIMENSIONS: Ø2-3/4 x H1/2"	☐ RECESSED WINDOW	☐ RECESSED SCOOP	☐ BLACK	☐ WHITE	☐ 3000K	CALCULATIONS WATTS: 2 QTY: = TOTAL WATTAGE:	
	☐ SURFACE MOUNT WINDOW	☐ SURFACE MOUNT SCOOP	☐ BRUSHED NICKEL				
 RD10 4W STEP LIGHT LS-RD10-4W DIMMABLE CUTOUT: 2-1/4" DIMENSIONS: Ø2-3/4 x H1/2"	☐ RECESSED WINDOW	☐ RECESSED SCOOP	☐ BLACK	☐ WHITE	☐ 2700K	☐ RGB	
	☐ SURFACE MOUNT WINDOW	☐ SURFACE MOUNT SCOOP	☐ BRUSHED NICKEL		☐ 3000K	☐ RGBW	
					☐ 4000K	☐ DTW	
						CALCULATIONS WATTS: 4 QTY: = TOTAL WATTAGE:	
						VOLTAGE: 12V DC WATTAGE: 4W SPREAD: 120° LUMENS: 320	



LED STEP LIGHTS

LED STEP LIGHTS		CHOOSE TRIM STYLE			CHOOSE FINISH		CHOOSE LIGHT COLOR		CALCULATIONS	
	RT05 STEP LIGHT LS-RT05LV DIMMABLE Standard single gang junction box	☐ WINDOW	☐ HORIZONTAL LOUVER	☐ SCREWLESS WINDOW	☐ BLACK	☐ WHITE	☐ 3000K	☐ RGB	VOLTAGE: 12V DC WATTAGE: 2.2W SPREAD: Varies LUMENS: 145	WATTS: 2.2 QTY: X TOTAL WATTAGE: =
		☐ SCOOB	☐ VERTICAL LOUVER	☐ SCREWLESS LOUVER	☐ BRUSHED NICKEL	☐ RGBW				

		CHOOSE FINISH		CHOOSE LIGHT COLOR		CALCULATIONS	
	RECESSED STEP LIGHT LS-RT05LV-RH DIMMABLE Standard single gang junction box	☐ BLACK	☐ WHITE	☐ 2700K	VOLTAGE: 12V AC/DC WATTAGE: 2W SPREAD: N/A LUMENS: 185	WATTS: 2 QTY: X TOTAL WATTAGE: =	
	SQ25 STEP LIGHT LS-SQ25-1W DIMMABLE CUTOUT: 1-1/2" DIMENSIONS: W2 x H1-3/8"	☐ BRUSHED NICKEL		☐ 3000K	VOLTAGE: 12V DC WATTAGE: 1W SPREAD: N/A LUMENS: 118	WATTS: 1 QTY: X TOTAL WATTAGE: =	
	RD25 STEP LIGHT LS-RD25-1W DIMMABLE CUTOUT: 1-1/2" DIMENSIONS: Ø2 x H1-3/8"	☐ MATTE BLACK	☐ WHITE	☐ 3000K	VOLTAGE: 12V DC WATTAGE: 1W SPREAD: N/A LUMENS: 118	WATTS: 1 QTY: X TOTAL WATTAGE: =	
	RD13 STEP LIGHT LS-RD13-3W DIMMABLE CUTOUT: 1-1/2" DIMENSIONS: Ø1-1/2 x H1-3/16"	☐ SATIN NICKEL		☐ 3000K (45° beam) ☐ 5000K (45° beam) ☐ RGBW (120° beam)	VOLTAGE: 12V DC WATTAGE: 3W SPREAD: 45°/120° LUMENS: 275	WATTS: 3 QTY: X TOTAL WATTAGE: =	
	RD21 STEP LIGHT LS-RD21 DIMMABLE CUTOUT: 5/8" DIMENSIONS: Ø3/4 x H7/8"	☐ MATTE BLACK	☐ WHITE	☐ 3000K	VOLTAGE: 12V DC WATTAGE: 0.5W SPREAD: 30° LUMENS: 68	WATTS: 0.5 QTY: X TOTAL WATTAGE: =	
		☐ BRUSHED NICKEL					
		☐ BLACK	☐ WHITE				
		☐ BRUSHED CHROME					

POWER SUPPLIES ADD 10% TO THE TOTAL WATTAGE FROM LED LIGHT SELECTION TABLE ABOVE ie: 12 x M1 Step Lights =12W, 6 x RD7 Cabinet Lights =12W.
 (WATTS X QTY = TTL WATTAGE) +10% =MIN. Required Wattage of Power Supply TOTAL Wattage: 12+12 =24W + 10% =26.4W minimum. MINIMUM 30W DRIVER IS REQUIRED.

	DRIVER	CODE	VOLTAGE	WATTAGE	OUTPUT	DIMENSIONS	CHOOSE WIRING	CALCULATIONS	QUANTITY
NON DIMMING	30W In/Outdoor LED Power Supply	LS-12V-30W-CV	120V AC (60Hz)	30W MAX Class 2	12V DC 2.5A	L6 ^{1/4} x W2 ^{5/16} x H3/4 in.	☒ HARDWIRE ☒ PLUG		
	60W In/Outdoor LED Power Supply	LS-12V-60W-O-CV	120V AC (50-60Hz)	60W MAX Class 2	12V DC 5A	L7 ^{7/16} x W1 ^{7/8} x H1 ^{5/16} in.	☒ HARDWIRE ☒ PLUG		
	96W In/Outdoor LED Power Supply	LS-12V-96W-O-CV	120V AC (50-60Hz)	96W MAX Class 2	12V DC 8A	L7 ^{5/16} x W2 ^{11/16} x H1 ^{3/4} in.	☒ HARDWIRE ☒ PLUG		
DIMMING	24W Dimmable LED Power Supply	LS-12V-24D-CV	120V AC (60Hz)	24W MAX Class 2	12V DC 2A	L6 ^{9/16} x W2 ^{1/8} x H13/16 in.	☒ HARDWIRE ☐ PLUG		
	48W Dimmable LED Power Supply	LS-12V-48D-CV	120V AC (60Hz)	48W MAX Class 2	12V DC 3.75A	L7 ^{1/8} x W2 ^{3/8} x H1 in.	☒ HARDWIRE ☐ PLUG		
	60W Dimmable LED Power Supply	LS-12V-60D-CV	120V AC (60Hz)	60W MAX Class 2	12V DC 5A	L7 ^{1/8} x W2 ^{3/8} x H1 ^{3/8} in.	☒ HARDWIRE ☐ PLUG		