

Solderless Connectors


3528



3528 120 density





5050



Curve





Aluminum Channels / Compatible Strip lighting* (Indoor/Outdoor/MP=Moisture Proof) and Solderless Connectors**





LS-LL8-L1 (1 meter) / LS-LL8-L2 (2 meter)

*3528 / 3528-OUT / 5050 / 5050-MP / 2835 / 2835-MP
**All connectors





LS-LL9-L1 (1 meter) / LS-LL9-L2 (2 meter)

*3528 / 3528-OUT / 5050 / 5050-MP / 2835 / 2835-MP
**Production lead or solder required





LS-LL10-L1 (1 meter) / LS-LL10-L2 (2 meter)

*3528 / 5050 / 5050-MP / 2835 / 2835-MP
**Production lead or solder required




LS-LL11-L1 (1 meter) / LS-LL11-L2 (2 meter)

*3528 / 5050 / 5050-MP / 2835 / 2835-MP
**Production lead or solder required





LS-LL13-L1 (1 meter) / LS-LL13-L2 (2 meter)

*3528 / 3528-OUT / 5050 / 5050-MP / 2835 / 2835-MP
**All connectors





LS-LL15-L1 (1 meter)

*3528 / 5050 / 5050-MP / 2835 / 2835-MP
**Production lead or solder required




LS-LL16-L1 (1 meter)

*3528 / 3528-OUT / 5050 / 5050-MP / 2835 / 2835-MP
**Production lead or solder required



LS-LL21-L1 (1 meter)

*3528 / 3528-OUT / 5050 / 5050-MP / 2835 / 2835-MP
**Production lead or solder required



LS-LL22-L1 (1 meter) / LS-LL22-L2 (2 meter)

*3528 / 3528-OUT / 5050 / 5050-MP / 2835 / 2835-MP
**Production lead or solder required

12V NON-DIMMING DRIVERS

	SKU	VOLTAGE	WATTAGE	OUTPUT	DIMENSIONS	WIRING:
15W LED Power Supply	LS-15W-Driver	120V AC	15W MAX Class 2	12V DC	L4.37 X W1.81 X H0.79 in.	<input checked="" type="checkbox"/> HARDWIRE <input checked="" type="checkbox"/> PLUG
30W Indoor/Outdoor LED Power Supply	LS-30W-0-Driver	100-265V AC	30W MAX Class 2	12V DC	L7.30 X W1.14 X H0.79 in.	<input type="checkbox"/> HARDWIRE <input checked="" type="checkbox"/> PLUG
60W Indoor/Outdoor LED Power Supply	LS-60W-0-Driver	100-265V AC	60W MAX Class 2	12V DC	L7.44 X W1.89 X H1.30 in.	<input type="checkbox"/> HARDWIRE <input checked="" type="checkbox"/> PLUG
150W Indoor/Outdoor LED Power Supply	LS-150W-0-Driver	120V AC	150W MAX	12V DC	L 9.4 x 2.80 x 1.77in	<input type="checkbox"/> HARDWIRE <input checked="" type="checkbox"/> PLUG
240W Indoor/Outdoor LED Power Supply	LS-240W-0-Driver	100-244V /277V	240W MAX	12V DC	L 9.6 x 2.70 x 1.54in	<input checked="" type="checkbox"/> HARDWIRE <input type="checkbox"/> PLUG

12V DIMMING DRIVERS

	SKU	VOLTAGE	WATTAGE	OUTPUT	DIMENSIONS	WIRING:
24W Dimmable Indoor LED Power Supply	LS-24D-CV	120V AC	24W MAX Class 2	12V DC	L6.10 X W2.13 X H0.79 in.	<input checked="" type="checkbox"/> HARDWIRE <input type="checkbox"/> PLUG
45W Dimmable Indoor LED Power Supply	LS-45D-CV	120V AC	45W MAX Class 2	12V DC	L7.09 X W2.4 X H0.98 in.	<input checked="" type="checkbox"/> HARDWIRE <input type="checkbox"/> PLUG
60W Dimmable Indoor LED Power Supply	LS-60D-CV	120V AC	60W MAX Class 2	12V DC	L7.09 x W2.36 x H1.38 in.	<input checked="" type="checkbox"/> HARDWIRE <input type="checkbox"/> PLUG
150W Dimmable Indoor/Outdoor LED Power Supply	LS-150W-Dim-CV	120V AC	150W MAX	12V DC	L9.8 x W3.0 x H3.0 in.	<input checked="" type="checkbox"/> HARDWIRE <input type="checkbox"/> PLUG
300W Dimmable Indoor/Outdoor LED Magnetic Power Supply	LS-300W-Dim-CV	120V AC	300W MAX	12V DC	L9.8 x W4.2 x H3.5 in.	<input checked="" type="checkbox"/> HARDWIRE <input type="checkbox"/> PLUG