

15M (50FT) LONG-RUN FLEXIBLE LED STRIP LIGHT

Long-Run series offers roll lengths up to 15M (50') with no voltage drop. Can be paired with single color controllers and dimmer.

Features

- No voltage drop for 15M (50')
- Commercial grade
- Highest quality 2835 SMD LEDs
- 24V DC input
- Excellent color output, CRI >90
- 930 lumens per meter
- Maximum Length: 10M (33')
- Cuttable every 96mm
- Dimmable with our dimmable low voltage power supplies

Applications

Accent | Display | Back Bar | Cove | Cabinet


Installation

Double-sided 3M tape on the back



Voltage	24V DC
Wattage	6W/M (1.8W/FT)
Roll Length	15M (50')
Cut Distance	6 LEDs - 96mm (3 ^{3/4} ")
# of LEDs	60 LEDs/M (3.28')
Color Temp	2700K / 3000K / 4000K
CRI	>90
Lumens	540/M (160/FT)
Beam Degree	120°
Dimmable	Yes
Lifespan	+65,000 hours
Warranty	5-year

Dimensions








Custom color temperature available: 2200K, 2700K, 3500K, 5000K, Red, Green, Blue.
Contact us for moisture proof or waterproof options.

Ordering Codes

	Product	Chip & Length	Voltage	LEDs/M	Color Temperature
LS -	FLI	2F	24	60	
	FLI : Indoor	2 : 2835 F : 15M (50')	24 : 24 volt	60 : 60 LEDs	27K : 2700K 3K : 3000K 4K : 4000K

Solderless Connectors

Solderless connectors are designed to provide a simple and quick connection for projects. Suitable for indoor applications.

Image	Code	Product	Description
	LS-SC1-2835	Seamless Connector	2 wire. Width: 5/8" (16mm). Application: Add length.
	LS-SC2-2835	Connector on one End	2 wire. Width: 5/8" (16mm). Applications: Cut strip to power.
	LS-SC3-2835	Connector on both Ends	2 wire. Width: 5/8" (16mm). Applications: For corners.
	LS-SC4-2835	L-Connector	2 wire. Width: 5/8" (16mm). Applications: For corners.
	LS-SC7-2835	Block Connector	2 wire. L7/16 x W3/8 x H5/16" (L11 x W10 x H8mm). Applications: For strip to strip or strip to power.