

## 2835 FLEXIBLE LED STRIP LIGHT

Ultra thin, high output LED strip for dry locations with roll lengths up to 5M (16.4'). Can be paired with single color controllers and dimmer.

### Features

- Highest quality 2835 SMD LEDs
- 24V DC input
- Excellent color output, CRI >90
- 1575 lumens per meter
- Maximum Length: 5M (16.4')
- Cuttable every 50mm
- Dimmable with our dimmable low voltage power supplies

### Applications


Accent | Display | Cove | Cabinet

### Installation


Double-sided 3M tape on the back



Indoor version:




Moisture Proof version




Voltage	24V DC
Wattage	14.4W/M (4.4W/FT)
Roll Length	5M (16.4')
Cut Distance	6 LEDs - 50mm (2")
# of LEDs	120 LEDs/M (3.28')
Color Temp	2700K / 3000K / 3500K / 4000K / 5000K
CRI	>90
Lumens	1575/M (475/FT)
Beam Degree	120°
Dimmable	Yes
Lifespan	+65,000 hours
Warranty	5-year

### Dimensions

Indoor version



Moisture Proof version








## Ordering Codes

		Product	Chip & Length	Voltage	LEDs/M	Color Temp
<b>Indoor</b>	LS -	FLI	2B	24	120	
		<b>FLI</b> : Indoor	<b>2</b> : 2835 <b>B</b> : 5M (16.5')	<b>24</b> : 24 volt	<b>120</b> : 120 LEDs	<b>27K</b> : 2700K
						<b>3K</b> : 3000K
						<b>35K</b> : 3500K
						<b>4K</b> : 4000K
						<b>5K</b> : 5000K
<b>Moisture Proof</b>	LS -	FLM	2B	24	120	
		<b>FLM</b> : Moisture Proof	<b>2</b> : 2835 <b>B</b> : 5M (16.5')	<b>24</b> : 24 volt	<b>120</b> : 120 LEDs	<b>3K</b> : 3000K
						<b>4K</b> : 4000K
						<b>5K</b> : 5000K

## Solderless Connectors

Solderless connectors are designed to provide a simple and quick connection for projects. Suitable for indoor/moisture proof applications.

Image	Code	Product	Description
	LS-SC1-2835	Seamless Connector	2 wire. Width: 5/8" (16mm). Application: Add length.
	LS-SC2-2835	Connector on one End	2 wire. Width: 5/8" (16mm). Applications: Cut strip to power.
	LS-SC3-2835	Connector on both Ends	2 wire. Width: 5/8" (16mm). Applications: For corners.
	LS-SC4-2835	L-Connector	2 wire. Width: 5/8" (16mm). Applications: For corners.
	LS-SC7-2835	Block Connector	2 wire. L7/16 x W3/8 x H5/16" (L11 x W10 x H8mm). Applications: For strip to strip or strip to power.

*Note: If using solderless connects on outdoor flexible strip the connection points must be properly sealed to prevent moisture entry. Heat shrink tubes and/or silicone is recommended. If not sealed properly, premature failure is possible.*