

## OUTDOOR RGB FLEXIBLE LED STRIP LIGHT

High output 5050 chips for outdoor locations with IP65 or IP67 protection.

### Features

- Moisture proof and weatherproof versions
- Highest quality 5050 SMD LEDs
- 12V DC & 24V DC input
- 4 wire system, requires RGB remote
- Maximum Length: 10M (32.8')
- Cuttable every 100mm or 200mm
- Dimmable with all our RGB controllers. Cannot be used with dimmable power supplies
- Moisture Proof includes transparent silicone jacket and double-sided 3M tape
- Weatherproof includes connectors on both ends, end caps, and mounting clips

### Applications

Cove | Mood | Display | Back Bar

### Installation

**Moisture proof** : Double-sided 3M tape on the back

**Weatherproof** : Mounting clips



Moisture Proof




Outdoor




Voltage	12V DC	24V DC
Wattage	7.2W/M (2.2W/FT)	
Roll Length	5M (16.4') / 10M (32.8')	10M (32.8')
Cut Distance	3 LEDs - 100mm (4")	6 LEDs - 200mm (8")
# of LEDs	30 LEDs/M (3.28')	
Color Temp	RGB color changing	
CRI	>90	
Lumens	410/M (125/FT)	
Beam Degree	120°	
Dimmable	Yes	
Lifespan	+65,000 hours	
Warranty	5-year	

### Dimensions

#### 12V version



#### 24V version








## Ordering Codes

		Product		Chip & Length		Voltage		LEDs/M		Color Temperature
<b>Moisture Proof</b>	LS -	FLM	-	5B	-	12	-	30	-	RGB
		<b>FLM</b> : Moisture Proof		<b>5</b> : RGB <b>B</b> : 5M (16.5')		<b>12</b> : 12 volt		<b>30</b> : 30 LEDs		<b>RGB</b> : Multi-color
<b>Outdoor</b>	LS -	FLO	-	5C	-		-	30	-	RGB
		<b>FLO</b> : Outdoor		<b>5</b> : RGB <b>C</b> : 10M (32.8')		<b>12</b> : 12 volt		<b>30</b> : 30 LEDs		<b>RGB</b> : Multi-color
						<b>24</b> : 24 volt				




## Solderless Connectors

Solderless connectors are designed to provide a simple and quick connection for projects. Suitable for indoor/outdoor applications.

Image	Code	Product	Description
	LS-RGB-SC1	Seamless Connector	4 wire. Width: 5/8" (16mm). Application: Add length.
	LS-RGB-SC2	Connector on one End	4 wire. Width: 5/8" (16mm). Applications: Cut strip to power.
	LS-RGB-SC3	Connector on both Ends	4 wire. Width: 5/8" (16mm). Applications: Corners.
	LS-RGB-SC4	L-Connector	4 wire. Width: 5/8" (16mm). Applications: For corners.
	LS-WPC-4	RGB Waterproof Connector	4 wire, male and female connector, solder on. L8 x W5/8" (L203 x 16mm). Applications: For corners or to add length.

*Note: If using solderless connects on outdoor flexible strip the connection points must be properly sealed to prevent moisture entry. Heat shrink tubes and/or silicone is recommended. If not sealed properly, premature failure is possible.*

## Accessories

Image	Code	Product	Description
	LS-EC-10MM	End Caps	For Single Color Outdoor Flexible LED Strip. Width: 3/8" (10mm). 5 pieces/bag.
	LS-UC-10MM	Mounting Clips	U-Clips for Single Color Outdoor Flexible LED Strip. Width: 3/8" (10mm). 20 pieces/bag, includes screws.
	LS-WPC-4	RGB Waterproof Connector	4 wire, male and female connector, solder on. L8 x W5/8" (L203 x 16mm). Applications: For corners or to add length.