

ARLO RECESSED IN-GRADE LIGHT



High power LED light engine with die cast brass housing uses fully replaceable MR16, available in 5W or 7W.

Features

- Directly wire to 12V AC/DC
- Die cast brass powder coated black finish
- 10° internal swivel tilt to direct light as needed

Applications

Landscape | Garden | Architectural | Accent

Installation

Recessed inground, Ø3^{5/8}" (92mm) cutout



Includes Outdoor MR16 LED Bulb

Choose wattage and color temperature

Specifications


Voltage	12-24V AC/DC (Includes MR16)	
Wattage	5W	7W
Lumens	550	800
Color Temp	2700K	2700K / 3000K
# of LEDs	6 Samsung LEDs	
CRI	>90	
Lifespan	+50,000 hours	
Beam Degree	45°	
Working Temp	-40°C~45°C (Enclosed MR16)	
IP	65	
Wire Length	20" (51cm)	
Housing	PC Housing with Brass Powder Coated Top	
Dimensions	Ø4 x 5 ^{3/8} " (102 x H137mm)	
Hole Cutout	Ø3 ^{5/8} " (92mm)	
Warranty	3-year	

Finishes Available



Black

Dimensions



ORDERING CODES


MR16 LED bulb and Uplight housing require separate ordering codes.

MR16 LED Bulb



Choose a MR16 bulb color temperature.

Image	Code	Product	Description
	LS-MR16-W-5W-27K	5W MR16 LED Bulb	12 AC/DC, 5W, L2 x Ø2" (L50 x Ø50mm)
	LS-MR16-W-7W-27K	7W MR16 LED Bulb	12 AC/DC, 7W, L2 x Ø2" (L50 x Ø50mm)
	LS-MR16-W-7W-3K		



Uplight Housing

Image	Code	Product	Description
	LS-IGUL-MR	Uplight Light Housing	Black PC Housing with wire lead (trim sold seperately)







Trim

Image	Code	Product	Description
	LS-IGUL-FT	Flat Trim	Powder coated black die cast brass, Ø4" (102mm)
	LS-IGUL-ST	Shade Trim	Powder coated black die cast brass, Ø4" (102mm)

Accessories

Image	Product	Code	Description
	100' Outdoor Wire	LS-OW-16-2-100	Outdoor wire for led lights. 16-2 AWG
	Outdoor Rated Marettes	LS-GEL-MAR	Outdoor rated, gel filled marettes ensure secure electrical connections in outdoor and wet conditions. Pack of 2.

Power Supplies

Image	Code	Voltage	Output Power	Class II	Dimmable Specs
Non-Dimmable					
	LS-12V-30W-O-CV	12V	Max. 30W	√	N/A
	LS-12V-60W-O-CV	12V	Max. 60W	√	N/A
	LS-12V-96W-O-CV	12V	Max. 96W	x	N/A
	LS-12AC-200W-LPS	12V AC	Max. 200W	x	Non dim outdoor transformer with built in photocell and timer
Dimmable					
	LS-12V-30D-MLT-CV	12V	Max. 30W	√	Triac/Phase. 0-10V, 1-10V, Potentiometer, 10V PWM 5 in 1 dimming
	LS-12V-60D-MLT-CV	12V	Max. 60W	√	Triac/Phase. 0-10V, 1-10V, Potentiometer, 10V PWM 5 in 1 dimming