




JOB#

DIM TO WARM LED STRIP LIGHTING

	LS-FLI-4B-24-224-DTW INDOOR 224 LEDs/M 24V DC 18W/M 5M 2016 Chips 62.5mm cut length W12 x H1.5mm
	LS-FLI-4B-24-224-DTW2 INDOOR 224 LEDs/M 24V DC 9W/M 5M 2016 Chips 62.5mm cut length W12 x H1.5mm
	LS-FLO-4B-24-224-DTW2 OUTDOOR 224 LEDs/M 24V DC 9W/M 5M 2016 Chips 62.5mm cut length W12 x H1.5mm



SOLDERLESS CONNECTORS



ALUMINUM CHANNELS

	Low Profile LS-LL11-L1 (1M) / LS-LL11-L2 (2M) W30 x H7mm Recessed or Surface mount		Slim Modern (For Indoor) LS-LL12-L1 (1M) / LS-LL12-L2 (2M) W18 x H8mm Recessed or Surface mount		Wide Modern LS-LL13-L1 (1M) / LS-LL13-L2 (2M) W23 x H10mm Recessed or Surface mount
	Mud In LS-LL23-DW-L3 (3M) W63 x H14mm Recessed		Thin Recessed LS-LL15-L1 (1M) / LS-LL15-L2 (2M) W25 x H7mm Recessed or Surface mount		Deep Recessed LS-LL16-L1 (1M) / LS-LL16-L2 (2M) W25 x H15mm Recessed or Surface mount

DIMMER & PLUG

	Dimmer LS-WD-WT Dimmer with switch & paddle wheel 120V AC, 60Hz, Single Pole 150W max load Fits single gang junction box		Plug LS-120V-SWITCH 8ft plug with rotary switch
--	---	--	---

	24V DRIVERS (cETLus)	CODE	VOLTAGE	WATTAGE	OUTPUT	DIMENSIONS	WIRING
DIMMING	24W Dimmable LED Power Supply	LS-24V-24D-CV	120V AC (60Hz)	24W MAX Class 2	24V DC 1A	L6 ^{9/16} x W2 ^{1/8} x H13/16 in.	<input checked="" type="checkbox"/> HARDWIRE <input type="checkbox"/> PLUG
	48W Dimmable LED Power Supply	LS-24V-48D-CV	120V AC (60Hz)	48W MAX Class 2	24V DC 2A	L7 ^{1/8} x W2 ^{3/8} x H1 in.	<input checked="" type="checkbox"/> HARDWIRE <input type="checkbox"/> PLUG
	60W Dimmable LED Power Supply	LS-24V-60D-CV	120V AC (60Hz)	60W MAX Class 2	24V DC 2.5A	L7 ^{1/8} x W2 ^{3/8} x H1 ^{3/8} in.	<input checked="" type="checkbox"/> HARDWIRE <input type="checkbox"/> PLUG
	96W Dimmable LED Power Supply	LS-24V-96D-CV	120V AC (60Hz)	96W MAX Class 2	24V DC 4A	L15 x W3 x H2 ^{1/4} in.	<input checked="" type="checkbox"/> HARDWIRE <input type="checkbox"/> PLUG
	150W Triac Dimmable LED Power Supply	LS-24V-150DE-CV	120V AC (47/63Hz)	150W MAX	24V DC 6.25A	L10 ^{1/4} x W4 ^{1/6} x H1 ^{13/16} in.	<input checked="" type="checkbox"/> HARDWIRE <input type="checkbox"/> PLUG
	300W Triac Dimmable LED Power Supply	LS-24V-300DE-CV	120V AC (47/63Hz)	300W MAX	24V DC 12.5A	L10 ^{1/4} x W4 ^{1/6} x H1 ^{13/16} in.	<input checked="" type="checkbox"/> HARDWIRE <input type="checkbox"/> PLUG

Plugs available separately